

# PVC slatwall panel

## Description:

- 1.Easy assembling, easy operation, bearing and tightly. Reducing the workload of workers, saving installation costs.
- 2.Compatible with standard slatwall accessories. All kinds of specifications applicable to different product and market demand.
- 3.Good texture and matt effect. Smooth inner surface.
- 4.Strong and durable. Waterproof, scratch and corrosion resistance, surface scratch can be easily repaired.
- 5.Non-lead, Non-toxic pollution, not containing harmful substances like formaldehyde, and so on.
- 6.Application:furniture making, such as shop fitting, display rack, storage cabinet, garage cabinet, hardware chain store, exclusive agent, exhibition, gallery, etc.
- 7.Good electric insulation, metal-free, and thermal stability.
- 8.Sound insulation, thermal insulation and stable performance.

## Product Specification:

Product	PVC Slotwall Panel
Size	Custom as clients requirement
Thickness	15~25mm,thickness Tolerance,+/-0.2mm
Face/Back	Melamine faced (one side or both side melamine faced), PVC,veneer,acrylic,fire-proof,UV
Surface Treatment	Matt, textured, glossy, embossed or magic
Slot Style	Ellipse, rectangle or trapezoid
Slot No.	7~21 slots or with one or two half slots on the side at your request
Slot Direction	2440mm direction or 1220mm direction
Accessory	Aluminium alloy T-bar (0.5~1mm thickness) or PVC T-bar
Core Material	Wood fiber (poplar, pine or combi)
Glue	E0, E1 or E2
Grade	A grade or as clients requirement
Density	730~750kg/m3
Usage &	MDF slatwall is widely used in supermarkets, shops, showrooms as shelves to

Performance	hang and display small commodities. With good properties, such as easy fabricability, anti-static, easy cleaning, long-lasting and no seasonal effect.
	Standard export pallet packing
MOQ	1x20'FCL
Supply Ability	5000cbm/month
Certification	ISO9001:2000,SGS



Product link : <http://www.rz-plastic.com/?p=973>